

JEH 乙丙橡胶绝缘氯磺化聚乙烯护套电机绕组引接电缆(电线)

JEH EPDM insulation CPS jacket motor leader wire

● PRODUCT DESCRIPTION

- Rated temperature: 90℃
- Rated voltage: 500V、1000v、3000v、6000v、10000v
- According to standard : QB/ZL080303-2008
- Stranded, tinned or bare cooper conductor
- EPDM insulation and CPS jacket
- For used leads wiring of B、E、F Insulation class motor

● 产 品 说 明

- 额定温度: 90℃
- 额定电压: 500V、1000v、3000v、6000v、10000v
- 执行标准: QB/ZL080303-2008
- 导体使用绞合镀锡丝或裸铜丝
- 乙丙橡胶绝缘氯磺化聚乙烯护套
- 用于 B、E、F 级电机引接线

NOM.AREA OF COND 标称截面	THICKNESS.INSULATION 绝缘标称厚度					THICKNESS.JACTET 护套标称厚度					MAX O.D 平均外径上限				
	mm					mm					mm				
	500V	1000 V	3000 V	6000 V	10000 V	500V	1000 V	3000 V	6000 V	10000 V	500V	1000 V	3000 V	6000 V	10000 V
mm <sup>2</sup>															
0.2	0.6	-	-	-	-	0.8	-	-	-	-	3.9	-	-	-	-
0.3	0.6	-	-	-	-	0.8	-	-	-	-	4.0	-	-	-	-
0.4	0.6	-	-	-	-	0.8	-	-	-	-	4.1	-	-	-	-
0.5	0.6	1.0	-	-	-	0.8	0.8	-	-	-	4.3	5.1	-	-	-
0.75	0.6	1.0	-	-	-	0.8	0.8	-	-	-	4.5	5.4	-	-	-
1.0	0.6	1.0	-	-	-	0.8	0.8	-	-	-	4.7	5.5	-	-	-
1.5	0.6	1.0	-	-	-	0.8	0.8	-	-	-	5.0	5.9	-	-	-
2.5	0.8	1.2	2.3	-	-	1.0	1.0	1.4	-	-	6.2	7.1	10.3	-	-
4	0.8	1.2	2.3	-	-	1.0	1.0	1.4	-	-	6.8	7.7	11.0	-	-
6	1.0	1.2	2.3	-	-	1.0	1.0	1.4	-	-	7.5	8.4	12.0	-	-
10	1.0	1.4	2.5	-	-	1.2	1.2	1.4	-	-	10.0	10.9	14.0	-	-
16	1.0	1.4	2.5	3.5	-	1.2	1.2	1.4	1.8	-	11.2	12.0	15.2	18.0	-
25	1.0	1.4	2.5	3.5	5.6	1.4	1.4	1.6	2.0	2.0	13.7	14.6	17.8	20.6	24.6
35	1.0	1.4	2.5	3.5	5.6	1.4	1.4	1.6	2.0	2.0	14.9	15.7	18.9	21.7	25.7
50	1.2	1.6	2.5	3.5	5.6	1.6	1.6	1.8	2.0	2.5	17.1	17.9	20.9	23.3	28.3
70	1.2	1.6	2.5	3.5	5.6	1.6	1.6	2.0	2.5	2.5	19.6	20.5	24.0	27.0	32.0
95	1.4	1.8	2.8	3.5	5.6	1.6	1.6	2.0	2.5	2.5	21.9	22.8	26.5	28.9	33.9
120	1.6	1.8	2.8	3.5	5.6	1.8	1.8	2.1	2.5	2.5	24.6	25	28.6	30.8	35.8
150	-	-	-	3.5	5.6	-	-	-	2.5	2.5	-	-	-	31.5	36.5
185	-	-	-	3.5	5.6	-	-	-	2.5	2.5	-	-	-	33.5	38.5
240	-	-	-	3.5	5.6	-	-	-	2.5	2.5	-	-	-	36.5	41.5

导体结构和导体电阻参照 JE、JH